

V I S

TOCCO SIGNORILE . A NOBLE TOUCH



LAFIENZA
TILE WITH STYLE

V I S

TOCCO SIGNORILE . A NOBLE TOUCH

Una contrapposizione voluta tra l'essenza più profonda del Brand, morbida ed accogliente, e la componente 'maschile', apparentemente opposta.

Un gioco di parole, curiosamente unite, che nella forma latina di 'forza', trovano l'unione: da una parte uno stile asciutto e minimale, dall'altro un'attenta ricerca, tipicamente femminile, delle nuance, dai timbri caldi ed avvolgenti. VIS rappresenta un attento studio sulle superfici e sui colori il cui plus sta nella capacità di richiamare su se stesso contemporaneamente l'essenza dell'intonaco, del cemento e al contempo la pura neutralità della tinta unita.

VIS, una proposta "premium" poiché incarna il massimo tecnologico ad oggi riconosciuto nell'ambito della produzione ceramica: un unico spessore sottile, il 6.5 mm, su tutti i formati che compongono la gamma, dalla lastra 120x278 fino al piccolo 30x60.

Una sola parola d'ordine: raffinatezza.

A deliberate contrast between the Brand's most profound, soft and welcoming essence and the apparently opposing 'masculine' component.

A curiously complicit play of words which, in their Latin form of 'strength', find union: on the one hand, a clean, minimalist style, on the other, an precise, typically feminine search for nuances with warm, enveloping tones. VIS is a careful study of surfaces and their colours whose bonus lies in the ability to simultaneously attract the essence of plaster and cement to itself and, at the same time, the pure neutrality of the solid colour.

VIS is a "premium" proposal as it encompasses the best technology currently available for tile production: a single slim thickness of 6.5 mm on all the formats in the range, from the 120x278 slab to the small 30x60.

In a word: sophistication.

V I S



VIS6 278PH RM - AE PAZ6 278 LP - YKSG6 2012B RM





V I S



VIS6 278PB RM - AE COL6 120 LPM

V I S



VIS6 278PB RM - AE VENG 120 LPM - AE VENG 278 LPM

V I S



VIS6 278AG RM - VIS6 12TP RM



VIS6 278AG RM - VIS6 278TP RM - VIS6 12TP RM

V I S



VIS6 120W RM - VIS6 12W RM



VIS6 120W RM - VIS6 12VM RM

V I S



VIS6 278A RM



V I S



VIS6 120TP RM - VIS6 278A RM

V I S



VIS6 120TP RM - VIS6 278A RM

V I S



VIS6 12VM RM



V I S



VIS6 278MG RM - VIS6 120MG RM




VIS6 90MG RM

VIS

COLOR BODY PORCELAIN TILE
GRES PORCELLANATO COLORATO IN MASSA


CONFORME - ACCORDING TO
UNI EN 14411 – G Bla



120x278
48"x110"



120x120
48"x48"



90x90
36"x36"



60x120
24"x48"



60x60
24"x24"



30x60
12"x24"

VIS

PB code info



VIS6 278PB RM 6,5 N ●

120x278 - 48"x110"



VIS6 120PB RM 6,5 N ●

120x120 - 48"x48"



VIS6 12PB RM 6,5 N ●

60x120 - 24"x48"



VIS6 90PB RM 6,5 N ●

90x90 - 36"x36"



VIS6 60PB RM 6,5 N ●

60x60 - 24"x24"



VIS6 36PB RM 6,5 N ●

30x60 - 12"x24"



MK.VIS6 30PB 6,5 N ●

30x30 - 12"x12"



MONOGRAM6 12
60x120 - 24"x48"



VIS

BC code info



VIS6 278BC RM 6,5 N ●

120x278 - 48"x110"



VIS6 120BC RM 6,5 N ●

120x120 - 48"x48"



VIS6 12BC RM 6,5 N ●

60x120 - 24"x48"



VIS6 90BC RM 6,5 N ●

90x90 - 36"x36"



VIS6 60BC RM 6,5 N ●

60x60 - 24"x24"



VIS6 36BC RM 6,5 N ●

30x60 - 12"x24"



MK.VIS6 30BC 6,5 N ●

30x30 - 12"x12"





120x278 - 48"x110"

VIS6 278PH RM 6,5 **N** ●

120x120 - 48"x48"

VIS6 120PH RM 6,5 **N** ●

60x120 - 24"x48"

VIS6 12PH RM 6,5 **N** ●

90x90 - 36"x36"

VIS6 90PH RM 6,5 **N** ●

60x60 - 24"x24"

VIS6 60PH RM 6,5 **N** ●

30x60 - 12"x24"

VIS6 36PH RM 6,5 **N** ●

30x30 - 12"x12"

MK.VIS6 30PH 6,5 **N** ●

120x278 - 48"x110"

VIS6 278BN RM 6,5 **N** ●

120x120 - 48"x48"

VIS6 120BN RM 6,5 **N** ●

60x120 - 24"x48"

VIS6 12BN RM 6,5 **N** ●

90x90 - 36"x36"

VIS6 90BN RM 6,5 **N** ●

60x60 - 24"x24"

VIS6 60BN RM 6,5 **N** ●

30x60 - 12"x24"

VIS6 36BN RM 6,5 **N** ●


30x30 - 12"x12"

MK.VIS6 30BN 6,5 **N** ●


VIS




VM code info

 VIS6 278VM RM 6,5 **N** ●


120x278 - 48"x110"

 VIS6 120VM RM 6,5 **N** ●


120x120 - 48"x48"

 VIS6 12VM RM 6,5 **N** ●

60x120 - 24"x48"

 VIS6 90VM RM 6,5 **N** ●

90x90 - 36"x36"

 VIS6 60VM RM 6,5 **N** ●

60x60 - 24"x24"

 VIS6 36VM RM 6,5 **N** ●

30x60 - 12"x24"


 MK.VIS6 30VM 6,5 **N** ●

30x30 - 12"x12"


VIS



TP code info

 VIS6 278TP RM 6,5 **N** ●

120x278 - 48"x110"

 VIS6 120TP RM 6,5 **N** ●

120x120 - 48"x48"

 VIS6 12TP RM 6,5 **N** ●

60x120 - 24"x48"

 VIS6 90TP RM 6,5 **N** ●

90x90 - 36"x36"

 VIS6 60TP RM 6,5 **N** ●

60x60 - 24"x24"








 VIS6 36TP RM 6,5 **N** ●

30x60 - 12"x24"








 MK.VIS6 30TP 6,5 **N** ●

30x30 - 12"x12"



A	code	✕	info
	VIS6 278A RM	6,5	N ●
120x278 - 48"x110"			
	VIS6 120A RM	6,5	N ●
120x120 - 48"x48"			
	VIS6 12A RM	6,5	N ●
60x120 - 24"x48"			
	VIS6 90A RM	6,5	N ●
90x90 - 36"x36"			
	VIS6 60A RM	6,5	N ●
60x60 - 24"x24"			
	VIS6 36A RM	6,5	N ●
30x60 - 12"x24"			
	MK.VIS6 30A	6,5	N ●
30x30 - 12"x12"			





W	code	✕	info
	VIS6 278W RM	6,5	N ●
120x278 - 48"x110"			
	VIS6 120W RM	6,5	N ●
120x120 - 48"x48"			
	VIS6 12W RM	6,5	N ●
60x120 - 24"x48"			
	VIS6 90W RM	6,5	N ●
90x90 - 36"x36"			
	VIS6 60W RM	6,5	N ●
60x60 - 24"x24"			
	VIS6 36W RM	6,5	N ●
30x60 - 12"x24"			
	MK.VIS6 30W	6,5	N ●
30x30 - 12"x12"			

VIS6 278AG RM 6,5  



120x278 - 48"x110"

VIS6 120AG RM 6,5  

120x120 - 48"x48"

VIS6 12AG RM 6,5  



60x120 - 24"x48"

VIS6 90AG RM 6,5  

90x90 - 36"x36"

VIS6 60AG RM 6,5  

60x60 - 24"x24"

VIS6 36AG RM 6,5  

30x60 - 12"x24"

MK.VIS6 30AG 6,5  


30x30 - 12"x12"

VIS6 278MG RM 6,5  

120x278 - 48"x110"

VIS6 120MG RM 6,5  

120x120 - 48"x48"

VIS6 12MG RM 6,5  

60x120 - 24"x48"

VIS6 90MG RM 6,5  

90x90 - 36"x36"

VIS6 60MG RM 6,5  

60x60 - 24"x24"

VIS6 36MG RM 6,5  

30x60 - 12"x24"

MK.VIS6 30MG 6,5  

30x30 - 12"x12"



V I S



VT56 120A RM - LOIRA6 2788 LPM

COLOR BODY PORCELAIN TILE - GRES PORCELLANATO COLORATO IN MASSA
CONFORME - ACCORDING TO
UNI EN 14411 – G Bla



PB MG AG W A

6x60 2.4"x24"			VIS6 BT60PB	VIS6 BT60MG	VIS6 BT60AG	VIS6 BT60W	VIS6 BT60A
6x90 2.4"x36"			VIS6 BT90PB	VIS6 BT90MG	VIS6 BT90AG	VIS6 BT90W	VIS6 BT90A
6x120 2.4"x48"			VIS6 BT120PB	VIS6 BT120MG	VIS6 BT120AG	VIS6 BT120W	VIS6 BT120A
120x32,5 48"x12.8"			VIS6 G120PB	VIS6 G120MG	VIS6 G120AG	VIS6 G120W	VIS6 G120A

CARATTERISTICHE TECNICHE SPECIFICHE - TECHNICAL FEATURES SPECIFICATIONS

	DIN EN 16165 Annex B (DIN 51130) (R)	DIN EN 16165 Annex A (DIN 51097) (A+B+C)	B.C.R. DM 14/6/89 N. 236		PENDULUM TEST BS (INGLESE)	PENDULUM TEST AS/NZS 4856:2004 (AUSTRALIANO)	PENDULUM TEST UNE ENV 12633:2003 (SPAGNOLO)	BOT 3000 (DCOF)
			c.a.	g.b.				
VIS	R10	A+B	>0,4	>0,4	>36	P3	1	>0,42

COLOR BODY PORCELAIN TILE - GRES PORCELLANATO COLORATO IN MASSA
CONFORME - ACCORDING TO
UNI EN 14411 – G Bla



BN BC PH TP VM

6x60 2.4"x24"			VIS6 BT60BN	VIS6 BT60BC	VIS6 BT60PH	VIS6 BT60TP	VIS6 BT60VM
6x90 2.4"x36"			VIS6 BT90BN	VIS6 BT90BC	VIS6 BT90PH	VIS6 BT90TP	VIS6 BT90VM
6x120 2.4"x48"			VIS6 BT120BN	VIS6 BT120BC	VIS6 BT120PH	VIS6 BT120TP	VIS6 BT120VM
120x32,5 48"x12.8"			VIS6 G120BN	VIS6 G120BC	VIS6 G120PH	VIS6 G120TP	VIS6 G120VM

IMBALLI - PACKING

FORMATO NOMINALE NOMINAL FORMAT	BORDO EDGE	SPESSORE THICKNESS	SCATOLA BOX			PALLET		
			PZ/ PCS	MQ/SM	KG	BOX/ BOXES	MQ/SM	KG
120x278 - 48"x110"	rectified	6,5	1	3,336	54,53	20	66,72	1110,60
120x120 - 48"x48"	rectified	6,5	2	2,88	45,44	30	86,40	1383,25
60x120 - 24"x48"	rectified	6,5	4	2,88	43,48	16	46,08	715,73
60x60 - 24"x24"	rectified	6,5	5	1,80	26,72	32	57,60	874,93
30x60 - 12"x12"	rectified	6,5	9	1,62	24,22	40	64,80	988,60
90x90 - 36"x36"	rectified	6,5	3	2,43	37,14	22	53,46	837,12
30x30 - 12"x12"	mosaic	6,5	6	0,54	7,48	72	38,88	558,42



VIS 90 W AS RM - VIS SB90 W AS



VTS 90MG AS RM

VIS 20MM



PB

MG

W

A



BN

BC

PH

TP

COLOR BODY PORCELAIN TILE - GRES PORCELLANATO COLORATO IN MASSA
CONFORME - ACCORDING TO
UNI EN 14411 - G Bla



PB MG W A

90x90 36"x36" 20

SQUARE BORDER* costa lucida
SQUARE BORDER* polished edge

△ T N ✕

VIS SB90PB AS VIS SB90MG AS VIS SB90W AS VIS SB90A AS



BN BC PH TP

90x90 36"x36" 20

SQUARE BORDER* costa lucida
SQUARE BORDER* polished edge

△ T N ✕

VIS SB90BN AS VIS SB90BC AS VIS SB90PH AS VIS SB90TP AS

* Angolari disponibili a richiesta. / Angle bracket available on request.



90x90
36"x36"

	VIS 90PB AS RM		VIS 90BN AS RM
	VIS 90MG AS RM		VIS 90BC AS RM
	VIS 90W AS RM		VIS 90PH AS RM
	VIS 90A AS RM		VIS 90TP AS RM

IMBALLI - PACKING











FORMATO NOMINALE NOMINAL FORMAT	BORDO EDGE	SPESSORE THICKNESS	SCATOLA BOX			PALLET		
			PZ/ PCS	MQ/SM	KG	BOX/ BOXES	MQ/SM	KG
90x90 - 36"x36"	rectified	20	1	0,81	36,99	30	24,30	1129,75

CARATTERISTICHE TECNICHE SPECIFICHE - TECHNICAL FEATURES SPECIFICATIONS

	DIN EN 16165 Annex B (DIN 51130) (R)	DIN EN 16165 Annex A (DIN 51097) (A+B+C)	B.C.R. DM 14/6/89 N. 236		PENDULUM TEST BS (INGLESE)	PENDULUM TEST AS/NZS 4856:2004 (AUSTRALIANO)	PENDULUM TEST UNE ENV 12633:2003 (SPAGNOLO)	BOT 3000 (DCOF)
			c.a.	g.b.				
VIS AS	R11	B+C	>0,4	>0,4	>36	P4	3	>0,42

CARATTERISTICHE TECNICHE SPECIFICHE GRES PORCELLANATO

TECHNICAL FEATURES SPECIFICATIONS

CARATTERISTICA Specification	METODO DI PROVA Test methods	REQUISITI PREVISTI DALLA NORMA Requirements in accordance to the standards	VALORE MEDIO IMOLA IMOLA average value
 DIMENSIONI E ASPETTO DIMENSIONS AND APPEARANCE	ISO 10545-2	PROSPETTO G.1 PROSPECT G.1	CONFORME COMPLIANT
 ASSORBIMENTO D'ACQUA WATER ABSORPTION	ISO 10545-3	≤ 0,5%	< 0,1%
 RESISTENZA A FLESSIONE FLEXURAL RESISTANCE		min. 35 N/mm ²	> 45 N/mm ²
 SFORZO DI ROTTURA MODULUS OF RUPTURE	ISO 10545-4	SPESSORE / THICKNESS ≥ 7,5 mm: min. 1300 N	6,5 mm 1800 N*
			SPESSORE* THICKNESS* 10 mm* 3000 N*
		SPESSORE / THICKNESS < 7,5 mm: min. 700 N	20 mm* 13000 N*
 RESISTENZA ALL'ABRASIONE PROFONDA DEEP ABRASION RESISTANCE	ISO 10545-6	≤ 175 mm ³	< 140 mm ³
 COEFFICIENTE DILATAZIONE TERMICA LINEARE (α) LINEAR EXPANSION THERMIC COEFFICIENT	ISO 10545-8	METODO DISPONIBILE AVAILABLE ON REQUEST	≤ 7x10 ⁻⁶ °C ⁻¹
 RESISTENZA AGLI SBALZI TERMICI RESISTANCE TO SUDDEN TEMPERATURE CHANGES	ISO 10545-9	METODO DISPONIBILE AVAILABLE ON REQUEST	RESISTE RESISTANT
 RESISTENZA AL GELO FROST RESISTANCE	ISO 10545-12	RICHIESTA ALWAYS TESTED	RESISTE RESISTANT
 PRODOTTI CHIMICI AD USO DOMESTICO ED ADDITIVI PER PISCINA HOUSEHOLD CHEMICALS AND SWIMMING POOL WATER CLEANSERS		min. B	min. B
ACIDI ED ALCALI A BASSA CONCENTRAZIONE ACIDS AND LOW CONCENTRATION ALKALIS	ISO 10545-13	DA LA, LB A LC FROM LA, LB TO LC / DE LA, LB A LC	DA LA, LB A LC FROM LA, LB TO LC / DE LA, LB A LC
ACIDI ED ALCALI AD ALTA CONCENTRAZIONE ACIDS AND HIGH CONCENTRATION ALKALIS		METODO DISPONIBILE AVAILABLE ON REQUEST	METODO DISPONIBILE AVAILABLE ON REQUEST
 RESISTENZA ALLE MACCHIE UGL STAIN RESISTANCE UGL		METODO DISPONIBILE AVAILABLE ON REQUEST	METODO DISPONIBILE AVAILABLE ON REQUEST
	ISO 10545-14		
RESISTENZA ALLE MACCHIE GL STAIN RESISTANCE GL		min. 3	min. 3

*VALORI RIFERITI AL FORMATO 60X60 / VALUES REFERRED TO 60X60 SIZE

